



MODEL 15.180 FD/FT

4x2 6m³ TIPPER & 4x2 TRUCK TRACTOR

- 15.180 FD/ MODEL

CAB

Cab Control Forward Tilt Cab
Seating Driver + 2 Passengers

Type/Extras Semi Sleeper with Aircon,
Suspension Seat

ENGINE

Make & Model FAW CA6DF2-18


Capacity 6 557 cm³

Layout & Type 6 cylinder in line, water cooled, turbo charged & intercooled

Emissions Standard Euro II
Power @ r/min (kW) 132 @ 2 300

Torque @ r/min (Nm) 650 @ 1 400 - 1 600





TRANSMISSION

 Make & Model
 FAW CA6TBX085

 Type
 6 Speed Manual Syncromesh

 Forward Ratios
 7.285, 4.193, 2.485, 1.563, 1.00, 0.820

 Reverse Ratio
 6.909

CLUTCH

Diameter 380 mm
Type Single Plate
Operation Hydraulic-Air Assisted

STEERING

Gear Ratio 20.48:1

Type Recirculating Ball

Operation Power Assisted

PERFORMANCE

Gradeability @ V Max 33%
Permissible Road Speed 80km/h

AXLES

Front Axle	I-section Beam (forged steel)
Rear Axle - Gearing Type	Full Floating - Single Reduction
Rear Axle Ratio	4.875:1

BRAKES

System Type Full Air - Dual Circuit with ABS
Park/Emergency
System Spring Brakes/Rear Booster

FUEL TANK

Number	One
Total Capacity	150 Litre

ELECTRICAL SYSTEM

System Voltage & Type	24V Negative Earth
No. of Batteries	Two X 12V

CHASSIS

Туре	Straight Ladder Type - Riveted
Front Suspension	Semi-Elliptical Leaf Springs with Double Acting Shock Absorbers
Rear Suspension	Semi-Elliptical Leaf Springs with Auxillary Springs

WHEELS

Tyre Size	275/70 R22.5 16PR
Rim Size	8.25 X 22.5
Туре	Tubeless Radial

MASS DATA	kg
Manufacturer's Gross Vehicle Mass (GVM)	15 000
Manufacturer's Gross Combination Mass (GCM)	24 000
Manufacturer's Front Axle Mass (GA Front)	5 500
Manufacturer's Rear Axle Mass (GAU Rear)	9 500
Permissible Gross Vehicle Mass (V)	14 500
Permissible Gross Combination Mass (D/T)	24 000
Permissible Front Axle Mass (A Front)	5 500
Permissible Rear Axle Mass (A Rear)	9 000
Unladen Front Axle Mass (A Front)	2 500
Unladen Rear Axle Mass (T Rear)	1 620
Unladen Mass Total (Tare)	4 120
Body and Payload Allowance	10 380

DIMENSIONS	mm
Wheelbase (WB)	3 510
Overall Length (OL)	5 822
Cab Length (A)	2 052
Overall Width (OW)	2 468
Overall Height (OH)	2 670
Front Overhang (D)	1 312
Rear Overhang (ROH)	1 000
Cab to Rear Axle (CA)	2 770
Recommended Body Length	3 528
Cab to End of Chassis (F)	3 770
Minimum Turning Radius	7 100
Minimum Turning Diameter	14 200
Ground Clearance	250
Track - Front	1 795
Track - Rear	1 860
Chassis Outer Width	865
Chassis Inner Width	680

The above specifications are not binding - subject to change without prior notice.

